

ROXATONE - SPECIFICATIONS

PRODUCT DESCRIPTION:

Water based multicolored seamless wall coating

PRODUCT OVERVIEW:

Roxatone is a spray applied multicolored paint that exhibits exceptional durability combined with a unique decorative appearance. It is an architectural coating designed for residential, retail, commercial, or institutional projects that require a decorative and washable finish. It is available in an unlimited range of color combinations as well as a variety of "quick-ship" pre-formulated Roxatone color selections.

SUITABLE APPLICATIONS:

Designed for application on interior surfaces such as; walls, trim and furniture. Can be applied over properly primed drywall, plaster, wood, metal, wallpaper, tile, concrete, formica, and previously painted or varnished surfaces.

UNSUITABLE APPLICATIONS:

Roxatone is not intended to be applied on exterior surfaces or any environment subjected to intense heat, moisture or abuse (floors).

APPLICATION METHOD:

Roxatone must be applied by conventional or HVLP spray equipment. This product cannot be rolled or brushed. Please consult the *Application Guide* for specific application and equipment information.

ENVIRONMENTAL INFORMATION:

Roxatone is a 100% acrylic water based product. It is virtually odorless and can be applied during regular business hours in occupied spaces. Roxatone has a V.O.C. content well below state regulations and is OTC compliant. The use of this product on new construction may assist in achieving LEED credits.

V.O.C. CONTENT:

ASTM D3960 – 90 gr/lit (max)

ODOR:

Very low odor

CLEAN UP:

Clean all equipment and spills with water

COVERAGE:

150 – 175 sq. ft/gallon

DRY TIME:

1 – 2 hrs to touch. 12 hours for use. 7 – 14 days full cure.

WASHABILITY:

ASTM D6141 – 2800 Cycles – No Wear

SCRUBABILITY:

ASTM D2486 – 5000 Cycles – Slight Wear
FED STD – 141A – 30,000 Cycles – No Wear

BACTERIAL RESISTANCE:

ASTM D3456 – No Growth

MILDEW RESISTANCE:

ASTM D3273 – No Growth

STAIN RESISTANCE:

Resistant to most household items such as; Juice, catsup, gasoline, butter, toothpaste, detergents, cooking oil, et.

FIRE RATING:

Class "A" Fire rating

FLASH POINT:

ASTM D56 – Not regulated

FINISH:

Low sheen – 10 @ 60 specular gloss

SURFACE PREPARATION:

Unpainted drywall must be primed with 2 coats of latex primer. Some projects may require a tinted primer as a base-coat, please call Roxatone tech support for tinting requirements. Painted surfaces must be sanded and primed with 1 coat high quality acrylic primer. Patches and repairs should be sanded and primed with 1 coat of high quality acrylic primer.

BATCH VARIATIONS:

Due to many variables involved with the manufacturing process of this coating, slight batch variations can be expected. Order sufficient quantities to avoid batch to batch variations.

NOTE:

Due to the many variables involved with the application method and manufacturing process of this coating, the finished product may vary slightly from the approved sample. A variance of less than 10% is considered normal for this type of coating.

WARRANTY:

Warranty is limited to the purchase of the product should it be proven defective.

STORAGE AND SHELF LIFE:

Keep Roxatone in a cool dry location. The shelf life of this product is approximately 12 months. **KEEP FROM FREEZING!**